



鞍豪实业（上海）有限公司

ANHAO INDUSTRIAL(SHANGHAI)CO.,LTD

Add: NO.679,Jianhe Road,Changning District,Shanghai,China

Technical Data Sheet

纳米碳酸钙 Nanoscale calcium carbonate AH302TDS 技术指标

外观/Appearance	白色粉末/white powder
粒子外形/particle shape	立方体/cubic
粒径（NM）/particle size nm	60-90
白度/whiteness	≥90
含水量%/ loss on drying	≤0.50
CaCO ₃ 含量% / CaCO ₃ content %	≥95
吸油值（Gdop/100g）/ oil absorption value g DOP/100gCaCO ₃	≤40
比表面积 BET/ specific surface area BET m ² /g	15-23
325 目（45um）筛余物%/ residue on 325 mesh screen %	/
盐酸不溶物% / insoluble matter in HCL %	/
表观密度（g/cm ² ）/ Apparent density	≤0.50
Ph 值 /Ph value	/
表面处理剂/ surface treatment	脂肪酸/ fatty acid
备注/ Remark	屈服值(Pa)100-200/Yield value

*应用领域 / application area: 汽车，船舶涂料，聚硫胶，聚氨酯胶，硅胶/ Car, ship paint. Polysulfide glue, polyurethane adhesive, silica gel

*功能特性/ Effect and benefits: 触变性好，抗流挂，易于分散。/ Good thixotropy, good sag resistance , easy to dispersed

